

Product No: TAC-W22-G5-R-C-0

ABB EV CHARGER 3P 415V 22kW WIFI, BLUETOOTH, RS485, 4G,& RFID WITH 5m CABLE TAC-W22-G5-R-C-0

FEATURES

- Type 2 EV compatibility
- 5m cable for flexible installation
- 3-Phase/32A fast charging
- RFID for secure access
- 4G connectivity for remote monitoring



General Information	
Brand	ABB
Product Type	Terra AC Wall Box
Technical Attributes	
Authentication Method	RFID App Free Vending
Communication Interface	Wi-Fi Ethernet Bluetooth Modbus 4G
Communication Protocol	OCPP1.6
Connection Configuration	TT, TN
EV Connectors	1 x AC Type 2
Input Current (A)	32A 3-Phase
Input Voltage (V)	380 – 420V AC 3-Phase
No. of Phases	3
Output Current (A)	32A AC 3-Phase
Output Voltage (V)	320 – 480V AC 3-Phase
Overcurrent Protection	40A
Overvoltage Category	III
Rated Frequency (Hz)	50/60



Physical Attributes	
Ambient Temperature Range (°C)	-30 to 50
Housing Material	Plastic
Mounting Type	Wall Mount
Storage Temperature Range (°C)	-50 to 80

Dimensions	
Cable Length (m)	5
Dimensions (mm)	195W x 110H x 320D
Weight (kg)	5.3

Protection & Standards	
Degree of Protection	IP54
Standards and Approvals	EN 61851-1 EN 61851-23 EN 61000-6-2 EN 61000-6-3 EN 301 908-2 IEC 60721-3-2: IE23 RoHS

Resources	
Product catalogue (Flipbook)	Download from here