



## SPD 1P T2 TNC 40kA

SPB140D

### Controls and indicators

Indicator lamp	Optic
----------------	-------

### Main electrical features

Rated operational voltage Ue	240 / 415 V
Frequency	50/60 Hz
Nominal discharge current (In) 8/20µs, IEC 61643)L-N(PEN)/ N-PE	20 kA

### Voltage

Maximum continuous operating voltage Uc	275 V
Voltage protection level Up according to IEC61643-1	1,35 kV
Voltage protection level Up L-PE/N-PE according to IEC61643-11	1,5 kV
Voltage level Up L-N/PEN IEC61643-11	1,35 kV
Maximum continuous operating voltage Uc_AC IEC61643	275 V

### Electric current

Calibration of the protection upstream	125 A
Max discharge I <sub>max</sub> (8/20µs, IEC 61643)	40 kA
Max discharge (I <sub>max</sub> ) L-N(PEN)/ N-PE	40 kA

### Electrical specifications

Short-circuit breaking capacity (I <sub>sc</sub> cr)	25 kA
--	-------

### Network configuration

Network type	TN-C
--------------	------

### Dimensions

Depth of installed product	58,2 mm
Height of installed product	89,8 mm
Width of installed product	17,7 mm

**Installation, mounting**

---

Tightening torque	3
-------------------	---

---

**Connection**

---

Connection cross-section of input and output with screws, for massive conductors	1,5 / 35 mm <sup>2</sup>
--	--------------------------

---

Connection cross section of access and exit with screws, for flexible conductor	1,5 / 25 mm <sup>2</sup>
---	--------------------------

---

**Equipment**

---

With remote signalling contact	no
--------------------------------	----

---

**Standards**

---

Approvals	KEMA
-----------	------

---

Test class IEC61643-11 / VDE0675-6-11	T2
---------------------------------------	----

---

European directive WEEE	concerned
-------------------------	-----------

---

**Use conditions**

---

Operating temperature	-40 80 °C
-----------------------	-----------

---