



Main

Range	SpaceLogic C-Bus
Product brand	Schneider Electric
Product name	DALI-2 gateway
Product or component type	Gateway
Device application	Light control
Colour	White

Complementary

Communication port protocol	C-Bus DALI-2
Module configuration	Programmed with C-Bus software
Software name	SpaceLogic C-Bus Commission
Input voltage	110...240 V AC at 50/60 Hz
Supply maximum power	13 W
Guaranteed current	0.23 A
Maximum current	0.25 A
Communication network type	C-Bus DALI
Connector type	2 RJ45
Connections - terminals	Screw terminals
Total number of 18 mm modules	6
Mounting support	DIN rail
Width	108 mm
Height	93 mm
Depth	63 mm

Environment

Ambient air temperature for operation	-5...45 °C
Ambient air temperature for storage	-20...80 °C
Product certifications	RCM CE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	0.359 kg
Package 1 Height	9.8 cm
Package 1 width	11.1 cm
Package 1 Length	15.6 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	10

Package 2 Weight	4.15 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins