

Product data sheet Characteristics

O3041HA-BK

Switch, Iconic Outdoor, 1ang, horizontal, 20A/16AX 250V, Black



Main

Range of product	Iconic
Range	Iconic
Product brand	Clipsal
Product or component type	Switch
Device presentation	Complete product
Device application	Lighting
Colour	Black (BK)
Plug, socket category	Low voltage
Outlet standard	Australian
Handle colour	Black

Complementary

Complementary	
Switch function	1-pole 1/2-way
Number of rocker	1
Number of poles	1
Number of gangs	1 gang
Device mounting	Surface
Mounting position	Horizontal
Mounting support	Wall
Fixing mode	By screws By clipping locks
Connections - terminals	Screw terminals 4 x 1.5 mm ² 2 x 2.5 mm ²
Material	PC (polycarbonate) TPE (thermoplastic elastomer) ABS (acrylonitrile butadiene-styrene) POM (polyoxymethylene)
Surface finish	Matt
Installation direction	Horizontal
Surface treatment	Untreated
Local signalling	without
[Ue] rated operational voltage	250 V AC 50 Hz
Rated current	20 A at 250 V AC 16 AX at 250 V AC
Clamping connection capacity	4 x 1.5 mm ² 3 x 2.5 mm ²
Screwdriver shape	Square drive no 1 (SQ1) Philips No 2
Wire stripping length	10 mm
Protection type	Without protection
Marking	Without marking
Height	85 mm
Width	115.5 mm
Depth	70 mm
Net weight	0.19 kg
Targeted country	Australia
Actuator	Rocker

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not interested for a set of or determining suitability or intelability of these products for specific user applications. It is the documentation is not integrator to perform the appropriate and complete risk analysis, evaluating of the products with respect to the relevant specific application or use thereof. Neither Schmeider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Ambient air temperature for operation	045 °C
IP degree of protection	IP56
Ambient air temperature for storage	060 °C
Relative humidity	1095 %
Electrical durability	12000 cycles
Standards	AS/NZS 3133

Offer Sustainability

REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant E EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Halogen content performance	Halogen free plastic parts product	

Life Is On