

# Product Environmental Profile

## Socket Sw Single with Timer 10A 250V XW






## General information

<b>Representative product</b>	Socket Sw Single with Timer 10A 250V XW - O3015T-XW
<b>Description of the product</b>	The product is the weatherproof switches and sockets. Mainly used outdoors, with water and skid resistance.
<b>Functional unit</b>	The connected socket outlet operates as a switch and a switched socket outlet during 10 years. It can optionally be configured as a delay timer/run-on timer, and features a scheduler function. The socket is available in 10A 250Vac to connect professional appliances, and complies with the standard AS/NZS 3112. The function unit is accordance with the following technical data: - IP54 - IK08



## Constituent materials

<b>Reference product mass</b>	282.3 g including the product, its packaging and additional elements and accessories
-------------------------------	--



Plastics	61.7%
Metals	9.5%
Others	28.9%



## Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 8 June 2011 and EU 2015/863) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium, flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers – PBDE), or phthalates (Bis(2-ethylhexyl) phthalate DEHP, Butyl benzyl phthalate -BBP, Dibutyl phthalate – DBP, Diisobutyl phthalate - DIBP) as mentioned in the Directive

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website

<http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page>



## Additional environmental information

The Socket Sw Single with Timer 10A 250V XW presents the following relevant environmental aspects


<b>Manufacturing</b>	Manufactured at a Schneider Electric production site ISO14001 certified
<b>Distribution</b>	Weight and volume of the packaging optimized, based on the European Union's packaging directive Packaging weight is 62.3 g, consisting of cardboard (82.3%), paper (17.7%)
<b>Installation</b>	Ref O3015T-XW does not require any installation operations.
<b>Use</b>	The product does not require special maintenance operations.
<b>End of life</b>	<p>End of life optimized to decrease the amount of waste and allow recovery of the product components and materials</p> <p>This product contains electronic card (26g) that should be separated from the stream of waste so as to optimize end-of-life treatment.</p> <p>The location of these components and other recommendations are given in the End of Life Instruction document which is available on the Schneider-Electric Green Premium website <a href="http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page">http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page</a></p> <p>Recyclability potential: <b>12%</b> Based on "ECO'DEEE recyclability and recoverability calculation method" (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).</p>



## Environmental impacts

<b>Reference life time</b>	10 years			
<b>Product category</b>	Combination of functions			
<b>Installation elements</b>	No special components needed			
<b>Use scenario</b>	The product is in active mode 20% of the time with a power use of 0.36W and in stand-by mode 80% of the time with a power use of 0.26W, for 10 years.			
<b>Geographical representativeness</b>	Australia			
<b>Technological representativeness</b>	The product is the weatherproof switches and sockets. Mainly used outdoors, with water and skid resistance.			
<b>Energy model used</b>	<b>Manufacturing</b>	<b>Installation</b>	<b>Use</b>	<b>End of life</b>
	Energy model used: China	Electricity mix; AC; consumption mix, at consumer; 240V; AU	Electricity mix; AC; consumption mix, at consumer; 240V; AU	Electricity mix; AC; consumption mix, at consumer; 240V; AU

Compulsory indicators		Socket Sw Single with Timer 10A 250V XW - O3015T-XW					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to mineral resources depletion	kg Sb eq	6.15E-04	6.15E-04	0*	0*	1.08E-07	0*
Contribution to the soil and water acidification	kg SO <sub>2</sub> eq	3.44E-02	6.17E-03	1.66E-04	1.41E-05	2.80E-02	8.10E-05
Contribution to water eutrophication	kg PO <sub>4</sub> <sup>3-</sup> eq	1.53E-02	7.84E-03	3.83E-05	3.42E-06	7.39E-03	3.02E-05
Contribution to global warming	kg CO <sub>2</sub> eq	2.94E+01	2.02E+00	3.64E-02	3.37E-03	2.73E+01	7.85E-02
Contribution to ozone layer depletion	kg CFC11 eq	5.49E-07	2.19E-07	7.38E-11	0*	3.28E-07	2.67E-09
Contribution to photochemical oxidation	kg C <sub>2</sub> H <sub>4</sub> eq	4.41E-03	5.87E-04	1.19E-05	1.05E-06	3.80E-03	7.72E-06
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Net use of freshwater	m <sup>3</sup>	4.00E-02	1.21E-02	0*	0*	2.78E-02	4.80E-05
Total Primary Energy	MJ	4.36E+02	3.44E+01	5.15E-01	4.41E-02	4.01E+02	3.69E-01



Optional indicators		Socket Sw Single with Timer 10A 250V XW - O3015T-XW					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to fossil resources depletion	MJ	4.05E+02	2.57E+01	5.12E-01	4.37E-02	3.78E+02	2.99E-01
Contribution to air pollution	m³	2.89E+03	2.61E+02	1.55E+00	0*	2.62E+03	2.72E+00
Contribution to water pollution	m³	1.71E+03	4.46E+02	5.99E+00	5.12E-01	1.25E+03	4.25E+00
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Use of secondary material	kg	7.13E-02	7.13E-02	0*	0*	0*	0*
Total use of renewable primary energy resources	MJ	1.18E+01	1.31E+00	0*	0*	1.05E+01	0*
Total use of non-renewable primary energy resources	MJ	4.24E+02	3.31E+01	5.14E-01	4.40E-02	3.90E+02	3.69E-01
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	1.11E+01	5.90E-01	0*	0*	1.05E+01	0*
Use of renewable primary energy resources used as raw material	MJ	7.15E-01	7.15E-01	0*	0*	0*	0*
Use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	4.19E+02	2.81E+01	5.14E-01	4.40E-02	3.90E+02	3.69E-01
Use of non renewable primary energy resources used as raw material	MJ	5.02E+00	5.02E+00	0*	0*	0*	0*
Use of non renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*
Use of renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*
Waste categories	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Hazardous waste disposed	kg	4.78E+00	3.51E+00	0*	0*	8.23E-01	4.50E-01
Non hazardous waste disposed	kg	7.13E+00	2.67E+00	1.29E-03	0*	4.46E+00	1.09E-03
Radioactive waste disposed	kg	1.33E-03	1.13E-03	9.22E-07	0*	1.93E-04	2.00E-06
Other environmental information	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Materials for recycling	kg	1.16E-01	2.68E-02	0*	6.20E-02	0*	2.76E-02
Components for reuse	kg	0.00E+00	0*	0*	0*	0*	0*
Materials for energy recovery	kg	1.81E-02	0*	0*	0*	0*	1.81E-02
Exported Energy	MJ	1.97E-04	1.85E-05	0*	1.79E-04	0*	0*

\* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version EIME v5.9.1, database version 2016-11 in compliance with ISO14044.

The use phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

<i>Registration number</i>	ENVPEP2106012_V1	<i>Drafting rules</i>	PCR-ed3-EN-2015 04 02
<i>Date of issue</i>	07/2021	<i>Supplemented by</i>	PSR-0005-ed2-EN-2016 03 29
<i>Validity period</i>	5 years	<i>Information and reference documents</i>	<a href="http://www.pep-ecopassport.org">www.pep-ecopassport.org</a>
<i>Independent verification of the declaration and data</i>			
Internal	X	External	
<i>The elements of the present PEP cannot be compared with elements from another program.</i>			
<i>Document in compliance with ISO 14021:2016 « Environmental labels and declarations - Self-declared environmental claims (Type II environmental labelling) »</i>			

Schneider Electric Industries SAS  
 Country Customer Care Center  
<http://www.schneider-electric.com/contact>  
 35, rue Joseph Monier  
 CS 30323  
 F- 92506 Rueil Malmaison Cedex  
 RCS Nanterre 954 503 439  
 Capital social 896 313 776 €  
[www.schneider-electric.com](http://www.schneider-electric.com)

Published by Schneider Electric

ENVPEP2106012\_V1

© 2019 - Schneider Electric – All rights reserved

07/2021