

Screw connector 40A 500V 3 x 6mm² with brass insert (x100)**Benefits**

- Suitable for earth connection.
- Brass coated that gives a better conductivity.
- Clear plastic material for a better connections control.

Norms

- > IEC 60998-2-1: 2002 ;
- IEC 60998-1: 2002
- > IP 20

GENERAL INFORMATION**Description**

Screw Connectors 40A.
For flexible and rigid cable up to 3 x 6 mm².

Application(s)

For flexible and rigid cable up to 3 x 6 mm². or 4 x 2.5 mm².

Technical details

Voltage (V) : 500.
Amperage (A) : 40.
Connection material : brass.
Plastic material : polycarbonate.
Glow wire test (°C) : 850.
Zinc plated steel screw M5 : Square + Philips (PH).
Application temperature : -35°C à 120°C.

LOGISTIC INFORMATION

Packaging



Carton box

Height (cm) : 8
 Length (cm) : 11
 Depth (cm) : 8.5
 Net weight (kg) : 0.43
 Gross weight (kg) : 0.45



Outer package 1



Carton box

Height (cm) : 18
 Length (cm) : 46
 Depth (cm) : 36
 Net weight (kg) : 13.76
 Gross weight (kg) : 14.4



x 32.00

Outer package 2



Pallet

Height (cm) : 125
 Length (cm) : 110
 Depth (cm) : 100
 Net weight (kg) : 495.36
 Gross weight (kg) : 569.4



x 1152.00