

**Screw connector 40A 500V 3 x 6mm<sup>2</sup> brass insert (x50)****Benefits**

- Suitable for earth connection.
- Brass coated that gives a better conductivity.
- Clear plastic material for a better connections control.

**Norms**

- > IEC 60998-2-1: 2002 ;
- IEC 60998-1: 2002
- > IP 20

**GENERAL INFORMATION****Description**

Screw Connectors 40A.  
For flexible and rigid cable up to 3 x 6 mm<sup>2</sup>.

**Application(s)**

For flexible and rigid cable up to 3 x 6 mm<sup>2</sup>. or 4 x 2.5 mm<sup>2</sup>.

**Technical details**

Voltage (V) : 500.  
Amperage (A) : 40.  
Connection material : brass.  
Plastic material : polycarbonate.  
Glow wire test (°C) : 850.  
Zinc plated steel screw M5 : Square + Philips (PH).  
Application temperature : -35°C à 120°C.

**LOGISTIC INFORMATION**

**Packaging**



**Plastic Jar**

Height (cm) : 13.5  
 Length (cm) : 8  
 Depth (cm) : 8  
 Net weight (kg) : 0.22  
 Gross weight (kg) : 0.26



**Outer package 1**



**Carton box**

Height (cm) : 14  
 Length (cm) : 42  
 Depth (cm) : 42  
 Net weight (kg) : 5.5  
 Gross weight (kg) : 7.5

x 25.00



**Outer package 2**



**Pallet**

Height (cm) : 115  
 Length (cm) : 126  
 Depth (cm) : 84  
 Net weight (kg) : 264  
 Gross weight (kg) : 375



x 1200.00