

LED double sided signal worklight rechargeable



Benefits

- Compact design for minimal footprint.
- Three different functions in one product (spot, wide, red LED).

Norms

> IP 54, IK 07

Compliance marks



GENERAL INFORMATION

Description

Double-sided LED rechargeable signal and mini floodlight.

Technical details

Power: 3 W + 5 W.

Luminous flux (lm): 500 (100%), 150 (30%).

Colour temperature: 4000 K and red LED.

Colour rendering index: 80.

Light beam: 10° and 120°.

Red LED mode: steady and strobe.

Materials: aluminum and polycarbonate.

360° swivel bracket.

Bracket: magnetic and with hooks.

Battery life: 3 hours (100%) to 10 hours (30%) and 20 hours (red LED).

Charging time: 4 hours.

Lithium battery: 3.7 V 2000 mAh.

Charger input voltage: 5 V DC 1 A.

Includes 1 m USB / Micro USB charging cable.

Weight (g): 170. Dimensions (cm): 7.8 x 7.2 x 5.

Advice

Recharge and discharge the battery completely for better battery lifetime.

Application(s)

Battery-powered temporary worksite light and signal.

Instructions

1. Button for selecting different modes (spot, wide, 30%, 100%, red LED, strobe).

LOGISTIC INFORMATION

Packaging



Carton box

Height (cm) : 12.5
 Length (cm) : 10
 Depth (cm) : 5.3
 Net weight (kg) : 0.18
 Gross weight (kg) : 0.21



Outer package 1



Carton box

Height (cm) : 17
 Length (cm) : 20.5
 Depth (cm) : 19.5
 Net weight (kg) : 2.51
 Gross weight (kg) : 2.66



x 12.00

Outer package 2



Carton box

Height (cm) : 18
 Length (cm) : 40.5
 Depth (cm) : 21.5
 Net weight (kg) : 5.32
 Gross weight (kg) : 5.82



x 24.00

Outer package 3



Pallet

Height (cm) : 100
 Length (cm) : 120
 Depth (cm) : 80
 Net weight (kg) : 314.28
 Gross weight (kg) : 329.28



x 1296.00