

Nylon hammer plug Ø 5 x 40 mm (x 100)



Characteristics

Drilling Ø (mm) : **5**
 Plug length (mm) : **40**
 Collar Ø (mm) : **9**
 Minimum drilling depth (mm) : **50**
 Tear-out resistance * C20/C25 concrete (daN*) : **110**
 Tear-out resistance brick (daN*) : **110**
 Concrete shearing resistance (daN*) : **110**
 Quantity per box : **100**

Materials

- ☑ Concrete
- ☑ Solid brick
- ☑ Stone

Benefits

- Simple and quick installation with a hammer!

GENERAL INFORMATION

Technical details

Polyamide 6.
 Reinforced flat collar.
 Delivered with 4.8 milled head zinc-plated steel screws PZ.

Application(s)

To attach chutes, raceways, corners, etc.

LOGISTIC INFORMATION

Packaging



Carton box

Height (cm) : 12
 Length (cm) : 9
 Depth (cm) : 6
 Net weight (kg) : 0.31
 Gross weight (kg) : 0.33



Outer package 1



x 18

Carton box

Height (cm) : 20
 Length (cm) : 30
 Depth (cm) : 30
 Net weight (kg) : 5.62
 Gross weight (kg) : 6.42



Outer package 2



x 720

Pallet

Height (cm) : 115
 Length (cm) : 120
 Depth (cm) : 80
 Net weight (kg) : 256.92
 Gross weight (kg) : 266.92

