

# SURFACE FITTINGS

## GLEAM, CCT3 SELECTABLE, DIMMABLE

14W

17W

CCT3

NEW!



### CONSTRUCTION:

- Aluminium powder coated housing
- Polystyrene opal diffuser

### FEATURES:

- Dimmable
- Comes in two diameter 300mm and 350mm
- Centre rear entry point
  - Large terminal block for easy install
  - Suitable for loop in/loop out
- Very high efficacy of 81-95lm/W



WARRANTY



RATED HOURS



LUMENS PER W



IK RATING



IP RATING



OPERATING VOLTAGE



BEAM ANGLE



CCT



SAFETY CLASS

	14W	17W
	<b>RGL14CCT3-01</b>	<b>RGL17CCT3-01</b>
<b>Comparable to:</b>	32W T8 Fluorescent	40W T8 Fluorescent
<b>Total Power (W):</b>	14.3/13.8/14.4	16.6/16/16.7
<b>Total Light Output (lm):</b>	1170/1320/1260	1430/1590/1540
<b>Efficacy (lm/cctW):</b>	82/96/89	87/100/93
<b>Lux at 1m (lux):</b>	280/310/300	360/400/390
<b>CCT (K):</b>	3000/4000/5700	3000/4000/5700
<b>Power Factor (PF):</b>	0.9	0.9
<b>Box Qty:</b>	8	6
<b>Weight (kg):</b>	0.5	0.7

### DIMENSIONS (mm)

	Diameter	Depth
RGL14CCT3-01	300	65
RGL17CCT3-01	350	65

