RMXRC240

Residual current circuit breaker, Resi MAX, 2P, 40A, 240V, 30mA, A type



Main	
Range	Resi MAX
Product or component type	Residual current circuit breaker (RCCB)
Product brand	Clipsal
Device application	Protection
Poles description	2P
Number of modules	2
[In] rated current	40 A
Network type	AC
Earth-leakage sensitivity	30 mA
Earth-leakage protection class	Type A
Rated conditional short- circuit current	6 kA

Complementary

Network frequency	50 Hz	
[Ue] rated operational voltage	240 V	
[Ui] rated insulation voltage	500 V	
[Uimp] rated impulse withstand voltage	4 kV	
Surge current	250 A	
Size	81 x 36 x 75 mm conforming to DIN 43880	
9 mm pitches	4	
Height	81 mm	
Width	36 mm	
Depth	73 mm	
Net weight	189 g	
Embedding depth	44 mm	
Colour	White	
Mechanical durability	4000 cycles	
Electrical durability	4000 cycles	
Connections - terminals	Tunnel type terminals - 125 mm² - flexible Tunnel type terminals - 135 mm² - rigid	
Wire stripping length	14 mm	
Tightening torque	3.5 N.m	

Environment

Standards	AS/NZS 61008	
Product certifications	RCM CB	
IP degree of protection	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529	
Pollution degree	2	
Overvoltage category	III	
Ambient air temperature for operation	-2540 °C	
Ambient air temperature for storage	-4085 °C	

Packing Units

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	212.0 g
Package 1 Height	8.0 cm
Package 1 width	4.0 cm
Package 1 Length	9.0 cm
Unit Type of Package 2	P06
Number of Units in Package 2	432
Package 2 Weight	106.0 kg
Package 2 Height	75.0 cm
Package 2 width	60.0 cm
Package 2 Length	80.0 cm
Unit Type of Package 3	S03
Number of Units in Package 3	54
Package 3 Weight	13.23 kg
Package 3 Height	30.0 cm
Package 3 width	30.0 cm
Package 3 Length	40.0 cm