

METAL FINDING

MetalliScanner® m40



Electronic Metal Detector with Wide Scan and Pinpoint Scan

MetalliScanner® m40 quickly and easily detects metal in wood, drywall, paneling, tile, stucco, plaster, concrete, and other non-metallic surfaces. It locates ferrous (magnetic) metal up to 4 inches (102 mm) deep and non-ferrous (non-magnetic) metal up to 2 inches (51 mm) deep.


MetalliScanner® m40 solves the very difficult problem of finding studs in lath and plaster walls. It works by finding the pattern of nails that attach the wood lath to the studs. MetalliScanner® m40 finds plumbing, ductwork, rebar, nails, and screws in your walls, floors, and ceilings, and is great for scanning reclaimed lumber for hidden metal.

MetalliScanner® m40 has two scanning positions, each with a progressive LED display. As it approaches a metal object, the red LEDs progressively light from the bottom up. The top lighted blue coil and an audio tone indicate when a metal target is located.

- Use Pinpoint Scan to locate small metal objects such as screws and nails
- Use Wide Scan to detect metal in walls or concrete
- · LED arrays indicate signal strength







SPECIFICATIONS

 $\label{eq:decomposition} \textbf{Dimensions} \qquad 7.65 \text{ in. L x 4.71 in. W x 0.98 in. H}$

(194 mm x 120 mm x 25 mm)

Weight 3.9 oz (111 g) without battery

Battery Type 9V alkaline (not included)

Depth* ½ in. Rebar: 4 in. (102 mm) (First Light) ½ in. Copper pipe: 2 in. (51 mm)

Operating 20° to 105°F (-7° to 41°C)

Uperating 20° to 105°F (-7° to 41°C) **Temperature**

Storage -20° to 150°F (-29° to 66°C)

Temperature

Humidity 5-90% RH non-condensing

Water Splash and water resistant, not

Resistance waterproof

*NOTE: See tool's instructions for more information. Sensing depth and accuracy can vary due to moisture, content of materials, wall texture, paint, etc.

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.

