

PV-LABEL KIT-DP

DESCRIPTION: SOLAR DC LABEL KIT: DISCONNECTION POINT

Technical Data

Part No.: PV-LABELKIT-DP

Material: Acrylic

Print Type: Laser Engraved

18MM

Adhesion: 3M 467MP

Protection: UV Guarantee to 4 Years as per IEC60068-2-5:2018

Compliance: Designed to AS/NZS5033:2021

SHUTDOWN PROCEDURE **WARNING. PV STRING** 37MM-1. Turn off the 'MAIN SWITCH (INVERTER SUPPLY) or 'INVERTER A.C. ISOLATOR' 2. Turn off the PV Array D.C. Isolator located at the **DISCONNECTION POINT** "WARNING" DO NOT OPEN PLUG AND SOCKET CONNECTORS OR PV STRING ISOLATOR UNDER LOAD - 150MM -120MM **WARNING. PV STRING** ←37MM. PV ARRAY D.C. ISOLATOR **+30MM DISCONNECTION POINT** PV ARRAY D.C. ISOLATOR 150MM -50MM **WARNING** INVERTER LOCATION 50MM 120MM INVERTER A.C. WARNING **ISOLATOR MULTIPLE SUPPLIES** 43MM 100MM AND CIRE 18MM **18MM** 65MM


Solar D.C. cables in conduit have been installed in the ceiling space.
The conduit is labelled 'SOLAR' and care must be taken while working nearby. The internal Solar D.C cables may be live and must not be disturbed or damaged.



200MM

200MM

WARNING



Issue Date: 9/12/21 Revision Date: 9/12/21 Authorised by: PV Connections