## 





#### LT SERIES LT4014TC/D - 14W

14 watt dimmable LED SMD tubular lamps, with selectable CCT

### Application

Energy efficient LED lamp solutions

#### **Design Specifications**

- Opal polycarbonate diffuser
- Poly covered aluminium body
- High efficiency LED optics, beam distribution 200 degree
- Integral dimmable LED driver
- Selectable CCT 3000K / 4000K / 6000K, CRI > 80
- Suits most CFL lamp fitting, lamp bases B22, E27, double insulation

#### Performance

- Dimmable YES
- Dimmer Type Trailing Edge









#### **Technical Specification**

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI
:	LT4014TC/B22D	240	14	1400/1750/1700	3000/4000/6000	80
	LT4014TC/E27D	240	14	1400/1750/1700	3000/4000/6000	80

Beam Angle (°)	Dimmable	Diameter (mm)	Length (mm)	Base Type
200	YES	42	133	B22
200	YES	42	133	E27

**IMPORTANT,** where CCT selection switching is provided, it is important to switch OFF the SUPPLY before the CCT selection is made, otherwise equipment damage may occur.

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".



# THE SFI SYSTEM ELIMINATES LED FLICKERING.

SIMPLY MATCH THE UNIFIT SFI DOWNLIGHT WITH THIS SDD400SFI DIMMER.







For related products please scan me





NSW/ACT: 02 9723 3099 QLD: 07 3879 5999 VIC/TAS/SA/NT: 03 9532 3168 WA: 08 9248 7458

© Copyright SAL - All Rights Reserved