


Product data sheet

Characteristics

42ELEDM2-VW

Rotary LED Dimmer, 40 Series Module, 150W, 240V AC, Vivid White



Main

Range	Clipsal Iconic
Product or component type	Dimmer
Device presentation	Mechanism
Dimmer type	Trailing edge
Colour tint	Vivid white (VW)
Type of packing	Box
Load type	Dimmable LED - 150 W Incandescent - 150 W



Complementary

Range compatibility	Clipsal Iconic
Fixing mode	Clip-in
Surface finish	Glossy
Ambient air temperature for storage	0...60 °C
Dimmer control	Rotary
[Ue] rated operational voltage	220...240 V AC 50 Hz 150 W
Function available	Brightness adjustment
Protection type	Short-circuit Overload protection Thermal protection
Ambient air temperature for operation	0...45 °C
Relative humidity	5...90 %
Connections - terminals	2-wire supply
Material	PC (UL94 V-2): top PC MAS056 (UL94 V-2): bottom
Height	22.84 mm
Width	22.84 mm
Depth	55.35 mm
Embedding depth	39 mm

Environment

Standards	AS/NZS 60669.2.1
IP degree of protection	IP20

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
