



## BUNKER 15 ROUND WITH SENSOR SL7272TC - 15W

LED 15 watt surface mount round shaped bunker, selectable CCT, IP54 with PIR sensor

### Application



A robust solution for residential and apartment interior or (covered eave) exterior utility spaces

### Design Specifications

- Durable UV resistant white or black polycarbonate body, opal polycarbonate diffuser
- Integral control gear, 15 watt with PIR sensor control, fixed 30 seconds ON
- Detection distance 7 metres diameter at 2.5hm, daylight threshold < 20 lux
- CRI >80, 1350/1450/1400lm, selectable CCT
- Quick connect installation design
- Double insulated, robust IK06 protection, wall or ceiling mount



### Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI
	SL7272TC/WH/S	240	15	1350/1450/1400	3000/4000/6500	80
	SL7272TC/BK/S	240	15	1350/1450/1400	3000/4000/6500	80

Beam Angle (°)	Body Colour	Diameter (mm)	Dim (mm)
110	WHITE	180	66(H)
110	BLACK	180	66(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

## Photometric Data

Unit: cd C0/C180 — C90/C270 —

**SL7272CW/WH/S at 4000K**

