



Main

Device short name	LA9G
Product or component type	Spreader
Accessory / separate part category	Connection accessories
Range compatibility	LC1G LR9G
Poles description	3P
Quantity per set	Set of 3

Complementary

[In] rated current	225 A
Connection pitch	45 mm
Net weight	0.4 kg
Product compatibility	LC1G115...225
Height	58.5 mm
Width	3 mm
Depth	24 mm

Environment

IP degree of protection	IP20 conforming to IEC 60529
Pollution degree	3 conforming to IEC 60947-1
Product certifications	cULus
Standards	EN/IEC 60947-1 UL 60947-1 CSA C22.2 No 60947-1 GB/T 14048
Ambient air temperature for operation	-40...60 °C
Ambient air temperature for storage	-60...80 °C
Operating altitude	3000 m without derating 5000 m with derating factor

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	264.0 g
Package 1 Height	3 cm
Package 1 width	12.5 cm
Package 1 Length	14 cm
Unit Type of Package 2	S02
Number of Units in Package 2	15
Package 2 Weight	4.381 kg
Package 2 Height	15 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
PVC free	Yes
Halogen content performance	Halogen free plastic parts product