
## LA9G3703

# Terminal shroud for TeSys Giga contactor LC1G630-800, 3 Pole, IP20





Terminal shroud
Installation accessories
3P
Set of 2

#### Complementary

Height	164 mm
Width	211 mm
Depth	115 mm
Net weight	0.165 kg
IP degree of protection	IP20 conforming to IEC 60529
Product compatibility	LC1G630800

#### Environment

Pollution degree	3 conforming to IEC 60947-1	
Standards	EN/IEC 60947-1 UL 60947-1 CSA C22.2 No 60947-1 GB/T 14048	
Operating altitude	3000 m without derating 5000 m with derating factor	
Ambient air temperature for storage	-4060 °C	
Ambient air temperature for operation	-6080 °C	

#### **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	966.0 g	
Package 1 Height	15 cm	
Package 1 width	30 cm	
Package 1 Length	40 cm	
Unit Type of Package 2	S02	
Number of Units in Package 2	1	
Package 2 Weight	966.0 g	
Package 2 Height	15 cm	
Package 2 width	30 cm	
Package 2 Length	40 cm	

### Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant E EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	China RoHS Declaration	
PVC free	Yes	
Halogen content performance	Halogen free plastic parts product	