



### Main

Product or component type	Phase barrier
Accessory / separate part category	Installation accessories
Poles description	3P
Quantity per set	Set of 2

### Complementary

Product compatibility	LC1G115...225 LC1G265...500 LC1G630...800
Height	2 mm
Width	115.5 mm
Depth	122 mm
Net weight	0.1 kg
[Ui] rated insulation voltage	1000 V

### Environment

Pollution degree	3 conforming to IEC 60947-1
Ambient air temperature for operation	-40...60 °C
Ambient air temperature for storage	-60...80 °C
Operating altitude	3000 m without derating 5000 m with derating factor
Standards	EN/IEC 60947-1 UL 60947-1 CSA C22.2 No 60947-1 GB/T 14048
Product certifications	ABS BV CB CCC CCS CUL CE DNV-GL EAC KC LROS (Lloyds register of shipping) RCM RINA RMRoS

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	150.0 g
Package 1 Height	2 cm
Package 1 width	115.5 cm
Package 1 Length	122 cm
Unit Type of Package 2	S02
Number of Units in Package 2	5
Package 2 Weight	750.0 g
Package 2 Height	15 cm
Package 2 width	30 cm
Package 2 Length	40 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
PVC free	Yes
Halogen content performance	Halogen free plastic parts product