



Main

| | |
|------------------------------------|------------------------|
| Device short name | LA9G |
| Product or component type | Terminal extension |
| Accessory / separate part category | Connection accessories |
| Range compatibility | LC1G LR9G |
| Poles description | 3P |
| Quantity per set | Set of 3 |

Complementary

| | |
|-----------------------|---------------|
| [In] rated current | 500 A |
| Connection pitch | 50 mm |
| Net weight | 0.77 kg |
| Product compatibility | LC1G400...500 |
| Height | 85 mm |
| Width | 3 mm |
| Depth | 30 mm |

Environment

| | |
|---------------------------------------|--|
| IP degree of protection | IP20 conforming to IEC 60529 |
| Pollution degree | 3 conforming to IEC 60947-1 |
| Product certifications | cULus |
| Standards | EN/IEC 60947-1 UL 60947-1 CSA C22.2 No 60947-1 GB/T 14048 |
| Ambient air temperature for operation | -40...60 °C |
| Ambient air temperature for storage | -60...80 °C |
| Operating altitude | 3000 m without derating 5000 m with derating factor |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 817.0 g |
| Package 1 Height | 85 cm |
| Package 1 width | 3 cm |
| Package 1 Length | 30 cm |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 8 |
| Package 2 Weight | 6.536 kg |
| Package 2 Height | 15 cm |

| | |
|------------------|-------|
| Package 2 width | 30 cm |
| Package 2 Length | 40 cm |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| PVC free | Yes |
| Halogen content performance | Halogen free plastic parts product |