Product data sheet Characteristics

GS1AH02

Direct rotary handle, TeSys GS, black handle, right side mounting, 2 positions I-O, for GS 100-400A IEC





Main

Range of product	TeSys
Range	TeSys
Device short name	GS1AH
Product or component type	Rotary handle
Range compatibility	TeSys GS GS1 J TeSys GS GS1 K TeSys GS GS1 L TeSys GS GS1 N TeSys GS GS1P TeSys GS GS1Q
Type of operating handle	Direct right side
Handle colour	Black

Complementary

Handle positions	O-I	
Rotary handle padlocking	With	
Switch rated current	100 A	
	125 A	
	160 A	
	250 A	
	315 A	
	400 A	
Standards	IEC	
Net weight	0.1 kg	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	85.9 g	
Package 1 Height	3 cm	
Package 1 width	8 cm	
Package 1 Length	17 cm	
Unit Type of Package 2	S02	
Number of Units in Package 2	20	
Package 2 Weight	2.066 kg	
Package 2 Height	15 cm	
Package 2 width	30 cm	
Package 2 Length	40 cm	
Package 3 Height	15 cm	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	☑ End Of Life Information	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

Contractual warranty

Warranty	18 months
----------	-----------