Main

Range of product	Altivar
Product or component type	Communication module

Complementary

Range compatibility	Altivar Machine ATV320	
Trange compatibility	Altivar 32	
	Altivar&NbspProcess ATV600	
	Altivar&NbspProcess ATV900	
	Altivar Machine ATV340	
Product compatibility	Variable speed drive	
Communication port protocol	Ethernet Powerlink	
Electrical connection	2 connectors RJ45, Ethernet	
Transmission rate	10/100 Mbps	
Display type	1 LED for MS (Module Status)	
	1 LED for NS (Network Status)	
	1 LED for TX/RX (Transmit/Receive port 1)	
	1 LED for TX/RX (Transmit/Receive port 2)	
Net weight	0.3 kg	

Packing Units

Unit Type of Package 1	PCE
	I OL
Number of Units in Package 1	1
Package 1 Weight	55.0 g
Package 1 Height	4.7 cm
Package 1 width	6.2 cm
Package 1 Length	9 cm
Unit Type of Package 2	S03
Number of Units in Package 2	100
Package 2 Weight	6.874 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration