

PRODUCT DATASHEET LED ECO BLADE BATTEN 600 MM 20W TRI HOME

LED ECO BLADE BATTEN | Slimline LED batten luminaires with slide switch for adjusting one of three selectable colours



Areas of application

- Offices, schools
- Retail
- Corridors
- Workshops
- Garages

Product benefits

- Available in 2 sizes
- Energy savings thanks to system efficacy of up to 100 lm/W
- Uniform light distribution thanks to opal diffuser

Product features

- Type of protection: IP20
- Replacement for traditional T8 luminaires
- Aluminium material with opal diffuser
- TRI CCT to fulfil different application needs
- 3 years warranty

TECHNICAL DATA

Electrical data

Nominal wattage	20.00 W
Nominal voltage	220240 V
Power factor λ	> 0.90
Protection class	T.

Photometrical data

Luminous flux	2000 lm
Luminous efficacy	100 lm/W
Color temperature	3000 5000 K
Color rendering index Ra	> 80
Beam angle	110°

Dimensions & Weight

Length	600.00 mm
Width	75.00 mm
Height	30.50 mm
Product weight	310.00 g

Materials & Colors

Product color	White
Housing color	White

Application & Mounting

Type of protection	IP20
Dimmable	No
Mounting type	Surface
Mounting location	Wall / Ceiling
Application environment	Indoor
LED module replaceable	Not replaceable

Lifespan

Lifespan L70/B50 at 25 °C	15000 h

DOWNLOAD DATA

DOWNLOAD DATA



IES file (IES)

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075706552	Folding box 1			
4058075706569	Shipping box 10	625 mm x 185 mm x 215 mm	4500.00 g	24.86 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.