

LEDVANCE VALUE Classic A

LED lamp in classic bulb shape

Highlights:

- Truwave Technology™ delivers less intense blue light for reduced eye strain
- Truwave LED mimics the natural light spectrum which supports an improved sleep/wake up cycle
- Ideal replacement of traditional incandescent bulb
- Energy saving >88%
- Long lifetime 15,000hrs
- Reliable product quality
- Over temperature protection

Applications:

- Table light
- Floor light
- Ceiling light
- Wall light
- Fan light
- Other indoor applications



PRODUCT INFORMATION

LED VALUE CLASSIC A With TruWave Technology™

Product Name	Product No. (EAN)	Model Number	W ¹		lm ¹	K	Ra	 ²		 [mm]	 d [mm]	 t [h] ³
LVCLA75 10W/827 230VFRB22D10X1G7TAULEDV	4058075732315	LDVCLA10W827B22FR	10	B22D	1055	2700	80	×	200°	118	60	15,000
LVCLA75 10W/827 230VFR E2710X1G7TAULEDV	4058075732339	LDVCLA10W827E27FR	10	E27	1055	2700	80	×	200°	118	60	15,000
LVCLA75 10W/865 230VFRB22D10X1G7TAULEDV	4058075732353	LDVCLA10W865B22FR	10	B22D	1055	6500	80	×	200°	117	60	15,000
LVCLA75 10W/865 230VFR E2710X1G7TAULEDV	4058075732377	LDVCLA10W865E27FR	10	E27	1055	6500	80	×	200°	117	60	15,000
LVCLA100 13W/827230VFRB22D10X1G7TAULEDV	4058075732254	LDVCLA13W827B22FR	13	B22D	1521	2700	80	×	200°	118	60	15,000
LVCLA100 13W/827 230VFRE2710X1G7TAULEDV	4058075732230	LDVCLA13W827E27FR	13	E27	1521	2700	80	×	200°	118	60	15,000
LVCLA100 13W/865230VFRB22D10X1G7TAULEDV	4058075732292	LDVCLA13W865B22FR	13	B22D	1521	6500	80	×	200°	117	60	15,000
LVCLA100 13W/865 230VFRE2710X1G7TAULEDV	4058075732278	LDVCLA13W865E27FR	13	E27	1521	6500	80	×	200°	117	60	15,000

¹ Typical values. All the technical parameters apply to the entire lamp. In view of the complex manufacturing process for light emitting diodes, the typical values given above for the technical LED parameters are merely statistical values that do not necessarily correspond to the actual technical parameters of an individual product; individual product may vary from the typical values. For parameter of Lumen and Watt, production control tolerance with $\pm 10\%$ in delivery

² The lamp is non-dimmable. Use with dimmer may lead to lamp flicker or product failure

³ L70B50 is the average operating life of the LED Lamp during which the luminous flux is greater than or equal to 70% of the initial luminous flux, for 50% of the population. The lifetime is estimated at room temperature (25deg C), free air burning, base up position