

PRODUCT DATASHEET

LED PFM CLAS P 4 W/6500 K B15d DIM GEN4

LED PERFORMANCE CLASSIC P DIMMABLE | LED lamps, classic mini-ball shape, with retrofit screw base



Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product benefits

- Very high dimmer compatibility, see also www.ledvance.com/dim
- Low energy consumption
- High color consistency thanks to narrow binning
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time
- No UV and near-IR radiation in the light beam
- Good quality of light
- Reliable operation thanks to brand quality

Product features

- Long lifetime: up to 25,000 h
- Color rendering index $R_a \geq 80$
- High color consistency: < 6 SDCM
- Luminous efficacy: up to 94 lm/W
- Mercury-free lamps



- Operating temperature from -20 °C to up to +40 °C, up to 95 % relative humidity

TECHNICAL DATA

Electrical data

Nominal wattage	4 W
Construction wattage	4.00 W
Nominal voltage	220...240 V
Claimed equiv. conventional lamp power	40 W
Nominal current	26 mA
Type of current	AC
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor λ	> 0.50

Photometrical data

Luminous flux	470 lm
Nominal useful luminous flux 90°	470 lm
Luminous efficacy	117 lm/W
Light color (designation)	Daylight
Color temperature	6500 K
Color rendering index Ra	80
Light color	865
Standard deviation of color matching	≤ 6 sdc _m

Light technical data

Beam angle	300 °
Starting time	< 0.5 s
Rated beam angle (half peak value)	300.00 °

Dimensions & Weight

Overall length	76.00 mm
Diameter	45.00 mm
Maximum diameter	45 mm
Product weight	16.00 g

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

Lifespan

Lifespan	15000 h
Number of switching cycles	50000

Additional product data

Base (standard designation)	B15d
Mercury content	0.0 mg

Capabilities

Dimmable	Yes
----------	-----

Certificates & Standards

Type of protection	IP20
Standards	CB / SAA

Country-specific categorizations

Order reference	LPCLPDIM 4W/865
-----------------	-----------------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	B15d
Length	76.00 mm
Height	45.00 mm
Width	45.00 mm

DOWNLOAD DATA

DOWNLOAD DATA	
<input type="checkbox"/>	PRODUCT DATASHEET

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075745759	Folding box 1	46 mm x 46 mm x 90 mm	34.00 g	0.19 dm ³
4058075745766	Shipping box 10	247 mm x 92 mm x 110 mm	440.00 g	2.50 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

