

LEDVANCE Value EM T8

Highlights:

- Truwave Technology™ delivers less intense blue light for reduced eye strain
- Truwave LED mimics the natural light spectrum which support
- Replacement of traditional T8 tube with G13 base
- Long lifetime, up to 30000hrs
- High lumen efficacy, up to 110lm/W
- Glass tube for high efficacy

Applications:

- Train Station
- Office
- Underground subway
- Supermarket, retail store
- Parking lot
- Warehouse



PRODUCT INFORMATION

Product Name	Product No. (EAN)	Model Number	W ¹	≡	lm ¹	K	Ra	⊙ ²	△	$\frac{l}{d}$ [mm]	d [mm]	t [h] ³
LVT8V-0.6M 8W/830 230V EM25X1G10TAULEDV	4058075733459	LDVT80.6M8W830	8	G13	850	3000K	80	×	160°	604	28	30000
LVT8V-0.6M 8W/840 230V EM25X1G10TAULEDV	4058075733473	LDVT80.6M8W840	8	G13	900	4000K	80	×	160°	604	28	30000
LVT8V-0.6M 8W/865 230V EM25X1G10TAULEDV	4058075733497	LDVT80.6M8W865	8	G13	900	6500K	80	×	160°	604	28	30000
LVT8V-1.2M 16W/830 230VEM25X1G10TAULEDV	4058075733510	LDVT81.2M16W830	16	G13	1700	3000K	80	×	160°	1214	28	30000
LVT8V-1.2M 16W/840 230VEM25X1G10TAULEDV	4058075733534	LDVT81.2M16W840	16	G13	1800	4000K	80	×	160°	1214	28	30000
LVT8V-1.2M 16W/865 230VEM25X1G10TAULEDV	4058075733558	LDVT81.2M16W865	16	G13	1800	6500K	80	×	160°	1214	28	30000
LVT8V-1.5M 20W/830 230VEM25X1G10TAULEDV	4058075733572	LDVT81.5M20W830	20	G13	2200	3000K	80	×	160°	1514	28	30000
LVT8V-1.5M 20W/840 230VEM25X1G10TAULEDV	4058075733596	LDVT81.5M20W840	20	G13	2300	4000K	80	×	160°	1514	28	30000
LVT8V-1.5M 20W/865 230VEM25X1G10TAULEDV	4058075733619	LDVT81.5M20W865	20	G13	2300	6500K	80	×	160°	1514	28	30000

¹ Typical values. All the technical parameters apply to the entire lamp. In view of the complex manufacturing process for light emitting diodes, the typical values given above for the technical LED parameters are merely statistical values that do not necessarily correspond to the actual technical parameters of an individual product; individual product may vary from the typical values. For parameter of Lumen and Watt, production control tolerance with $\pm 10\%$ in delivery

² LED lamps can be operated with a wide variety of commercially-available dimmers; details and results of compatibility tests can be seen at www.ledvance.com/dim and in the additional technical product information sheets linked there

³ L70B50 is the average operating life of the LED Lamp during which the luminous flux is greater than or equal to 70% of the initial luminous flux, for 50% of the population. The lifetime is estimated at room temperature (25deg C), free air burning, base up position