

PRODUCT DATASHEET LED PERFORMANCE STICK 11 W/4000 K E27 DIM

LED PERFORMANCE STICK | LED lamps, classic stick shape



Areas of application

- Suitable for indoor applications
- Replacement for conventional compact fluorescent lamps with wattage 11 W, 15 W and 24 W

Product benefits

- Creation of the preferred light ambience thanks to dimming
- Wide beam angle: 200°
- Instant 100 % light, no warm-up time
- Stylish and modern design
- No UV and near-IR radiation in the light beam
- Reliable operation thanks to brand quality

Product features

- Dimmable (with many common dimmers, see also www.ledvance.com/dim)
- Long lifetime: up to 25,000 h
- Mercury-free lamps
- Input voltage: 220...240 V_{AC}
- Storage temperature from -20 °C to up to +80 °C, up to 95 % relative humidity



January 04, 2023, 03:06:43 LED PERFORMANCE STICK 11 W/4000 K E27 DIM - Operating temperature from -20 °C to up to +35 °C, up to 95 % relative humidity

TECHNICAL DATA

Electrical data

| Nominal wattage | 11 W |
|--|----------|
| Construction wattage | 11.00 W |
| Nominal voltage | 220240 V |
| Claimed equiv. conventional lamp power | 75 W |
| Nominal current | 55 mA |
| Type of current | AC |
| Operating frequency | 50/60 Hz |
| Mains frequency | 50/60 Hz |
| Power factor λ | > 0.70 |

Photometrical data

| Luminous flux | 1050 lm |
|---|------------|
| Nominal useful luminous flux 90° | 1050 lm |
| Luminous efficacy | 95 lm/W |
| Lumen main.fact.at end of nom.life time | 0.70 |
| Light color (designation) | Cool White |
| Color temperature | 4000 K |
| Color rendering index Ra | ≥80 |
| Light color | 840 |
| Standard deviation of color matching | ≤6 sdcm |

Light technical data

| Beam angle | 200 ° |
|------------------------------------|----------|
| Starting time | < 0.5 s |
| Rated beam angle (half peak value) | 200.00 ° |

Dimensions & Weight

| Overall length | 121.00 mm |
|------------------|-----------|
| Diameter | 46.00 mm |
| Maximum diameter | 46 mm |
| Product weight | 35.00 g |

Temperatures & operating conditions

| Ambient temperature range | -20+30 °C |
|---------------------------|-----------|
| , , | |



Lifespan

| Lifespan | 15000 h |
|----------------------------|---------|
| Number of switching cycles | 100000 |

Additional product data

| Base (standard designation) | E27 |
|-----------------------------|--------|
| Mercury content | 0.0 mg |

Capabilities

| Dimmable Yes |
|--------------|
|--------------|

Certificates & Standards

| Type of protection | IP20 |
|--------------------|----------|
| Standards | CB / SAA |

Country-specific categorizations

| Order reference | LP STICK DIM11W |
|-----------------|-----------------|
| | |

Energy labelling regulation data acc EU 2019/2015

| Light source cap-type (or other electric interface) | E27 |
|---|-----------|
| Length | 121.00 mm |
| Height | 46.00 mm |
| Width | 46.00 mm |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075731936 | Folding box 1 | 47 mm x 47 mm x 121 mm | 48.00 g | 0.27 dm³ |
| 4058075731943 | Shipping box 10 | 246 mm x 103 mm x 138 mm | 577.00 g | 3.50 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.