



The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.



## Main

Range of product	PowerLogic
Product name	PowerTag M630
Product or component type	Energy sensor
Poles	3P
Maximum current [Imax]	630 A
[Ib] basic current	100 A
Starting current	400 mA
Saturation current	1260 A
Product specific application	Energy management Overload alarm Power factor Load monitoring Circuit monitoring
Concentrator compatibility	Acti9 Smartlink SI B Acti9 Smartlink SI D Acti9 PowerTag Link C Acti9 PowerTag Link Acti9 PowerTag Link HD Harmony Hub Wiser IP module EcoStruxure Panel Server Universal EcoStruxure Panel Server Advanced PrismaSet Active
Range compatibility	Compact NSX Compact NSX400...630 Compact NS Compact NS400/630 TeSys TeSys GV6 EasyPact EasyPact CVS400 EasyPact EasyPact CVS630
Type of measurement	Active and reactive energy Active and reactive power Apparent power Current Voltage Power factor
Accuracy class	Class 1 active energy conforming to IEC 61557-12 Class 2 reactive energy conforming to IEC 61557-12 Class 1 active power conforming to IEC 61557-12 Class 2 reactive power conforming to IEC 61557-12 Class 2 apparent power conforming to IEC 61557-12 Class 1 current conforming to IEC 61557-12 Class 0.5 voltage conforming to IEC 61557-12 Class 1 power factor conforming to IEC 61557-12
Metering type	Power factor 0...1: class 1 at 25 °C conforming to IEC 61557-12 Active energy Ep IN/OUT/tot 0...281 x 10exp(9) kWh: class 1 at 25 °C conforming to IEC 61557-12 Reactive energy Ep IN/OUT/tot 0...281 x 10exp(9) kVARh: class 2 at 25 °C conforming to IEC 61557-12 Voltage U12, U23, U31 320...480 V: class 0.5 at 25 °C conforming to IEC 61557-12 Voltage V1N, V2N, V3N 184...276 V: class 0.5 at 25 °C conforming to IEC 61557-12 Apparent power S, S1, S2, S5 221 VA...1048 kVA: class 2 at 25 °C conforming to IEC 61557-12 Active power P, P1, P2, P5 221 W...1048 kW: class 1 at 25 °C conforming to IEC 61557-12 Reactive power Q, Q1, Q2, Q5 221 VAR...1048 kVAR: class 2 at 25 °C conforming to IEC 61557-12 Current I1, I2, I3, Iavg 20...630 A: class 1 at 25 °C conforming to IEC 61557-12 Frequency 45...65 Hz
Mounting location	Bottom
Mounting support	On circuit breaker
Connection pitch	45 mm
Product destination	Switchboard
Event management	Voltage loss with measured current at voltage loss

Transmission support medium	Radio frequency 2.4...2.4835 GHz conforming to IEEE 802.15.4 (11...26) transmission time < 5 ms
Emission power	10 mW

## Complementary

[Imp] maximum permanent current	1.2 x I <sub>n</sub>
Mounting mode	Bolt-on
Tightening torque	50 N.m
Supply voltage	230 V AC, +/- 20 %, between phase and neutral 400 V AC, +/- 20 %, between phases
Network frequency	50 Hz 60 Hz
Maximum power consumption	3.7 VA
Standards	IEC 61557-12 IEC 61010 ETSI EN 301 487-1
Height	91 mm
Width	140 mm
Depth	110 mm
Net weight	800 g
Colour	Dark grey (RAL 7016)

## Environment

Quality labels	CE
Directives	2014/53/EU - radio equipment directive
Operating altitude	0...2000 m
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C
Overvoltage category	IV conforming to IEC 61010-1
Measurement category	Category III conforming to IEC 61010-2-030
IP degree of protection	IP20
IK degree of protection	IK07 conforming to IEC 60068-2-75 test Ehb
Pollution degree	3
Relative humidity	0...95 % at 55 °C conforming to IEC 60721-3-3
Vibration resistance	3M4 conforming to IEC 60721-3-3
Electromagnetic compatibility	Industrial electromagnetic environment conforming to IEC 61326-1 Radiated EMC conforming to ETSI EN 301 489-17 Electromagnetic emission conforming to IEC 62311
Environmental characteristics	Indoor use

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.06 kg
Package 1 Height	15 cm
Package 1 width	12 cm
Package 1 Length	17 cm
Unit Type of Package 2	S02
Number of Units in Package 2	2
Package 2 Weight	2.47 kg
Package 2 Height	15 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Unit Type of Package 3	P06
Number of Units in Package 3	32
Package 3 Weight	44.0 kg
Package 3 Height	73 cm

Package 3 width	60 cm
Package 3 Length	80 cm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>

### Contractual warranty

Warranty	18 months
----------	-----------