

# PRODUCT DATASHEET LINE R7s 78.00 mm 75 9.5 W/2700 K R7s

LED LINE R7S DIM | Dimmable LED lamps with retrofit base R7s



#### Areas of application

- General illumination within ambient temperatures from -20...+40 °C
- Outdoor use in suitable outdoor luminaires only

#### **Product benefits**

- Fits into most R7s luminaires thanks to excentric base
- Good all-around light emission
- Lower thermal output (compared with the standard reference product)
- Very long lifetime of up to 25,000 h
- Four year guarantee

#### **Product features**

- Dimmable (with many common dimmers, see also www.ledvance.com/dim)
- LED alternative to conventional R7s lamps
- Good quality of light; color rendering index R $_{\rm a}$ :  $\geq$  80; constant chromaticity






# **TECHNICAL DATA**

# Electrical data

Nominal wattage	9.5 W
Construction wattage	9.50 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	75 W
Nominal current	42 mA
Type of current	AC
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor λ	≥ 0.50

# Photometrical data

Luminous flux	1055 lm
Nominal useful luminous flux 90°	1055 lm
Luminous efficacy	111 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.4







# Light technical data

Beam angle	300 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s
Rated beam angle (half peak value)	300.00 °

# **Dimensions & Weight**

Overall length	78.00 mm
Diameter	28.00 mm
Maximum diameter	28 mm
Product weight	52.00 g

# Temperatures & operating conditions

# Lifespan

Lifespan	25000 h
Number of switching cycles	100000
Lumen maintenance at end of serv	0.70
Rated lamp survival factor at 6,000	≥ 0.90

# Additional product data

Base (standard designation)	R7s
Mercury content	0.0 mg

# **Capabilities**

		Dimmable	Yes
--	--	----------	-----

### Certificates & Standards

Energy efficiency class	E
Energy consumption	10.00 kWh/1000h
Type of protection	IP20
Standards	СВ

Photobiological safety group acc. to EN62778	RG1		
Country-specific categorizations			
Order reference	LEDLI7875 9,5W/		
Energy labelling regulation data acc EU 2019/2015			
Lighting technology used	LED		
Non-directional or directional	NDLS		
Mains or non-mains	MLS		
Light source cap-type (or other electric interface)	R7s		
Connected light source (CLS)	No		
Color-tuneable light source	No		
Envelope	No		
High luminance light source	No		
Anti-glare shield	No		
Correlated colour temperature type	SINGLE_VALUE		
Standby power	0.00 W		
Networked standby power for CLS	0 W		
Claim of equivalent power	Yes		
Length	78.00 mm		
Height	28.00 mm		
Width	28.00 mm		
Chromaticity coordinate x	0.458		
Chromaticity coordinate y	0.410		
R9 Colour rendering index	0.00		
Beam angle correspondence	SPHERE_360		
Survival factor	0.90		
LED light source replaces a fluorescent light source	No		
EPREL ID	522899		
Model number	AC32130		

# Safety advice

- To ensure full light efficiency and product lifetime, it is recommended to detach any glass or cover of the luminaire.

# **LOGISTICAL DATA**





Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075711105	Folding box 1	39 mm x 29 mm x 82 mm	63.00 g	0.09 dm <sup>3</sup>
4058075711112	Shipping box 10	153 mm x 86 mm x 96 mm	719.00 g	1.26 dm <sup>3</sup>
4058075711129	Shipping box 80	316 mm x 182 mm x 206 mm	6173.00 g	11.85 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### References / Links

- For Guarantee see www.osram-lamps.com/guarantee
- For further products and actual information concerning LED lamps see www.osram-lamps.com/led-lamps

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



