



Main

| | |
|---------------------------|--------------|
| Range | Acti9 |
| Product or component type | Chassis |
| Device application | Distribution |

Complementary

| | |
|--|--|
| Incomer device | Switch disconnecter - 3P MCCB - 3P |
| Protection device type | Miniature circuit breaker (MCB) as outgoer Residual current circuit breaker with overcurrent protection (RCBO) as outgoer |
| Network type | AC |
| [In] rated current | 400 A |
| Number of ways | 1 way (incomer) - 3P 1 way (outgoer) - 1P or 3P |
| Rated voltage | 415 V 50 Hz |
| Short-circuit withstand | 25 kA 0.1 s |
| [Ui] rated insulation voltage | 500 V |
| [Uimp] rated impulse withstand voltage | 6 kV |
| Number of poles | 48 |
| Number of poles | 48 x 18 mm |
| Width | 245 mm |
| Length | 718 mm |
| Depth | 95 mm |
| Net weight | 4.44 kg |
| Busbar pitch | 18 mm |
| Location of connection | Dual feed |

Environment

| | |
|-----------|--------------|
| Standards | AS/NZS 61439 |
|-----------|--------------|

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Package 1 Length | 71.8 cm |
| Number of Units in Package 1 | 1 |
| Package 1 Width | 24.5 cm |
| Package 1 Height | 9.5 cm |
| Package 1 Weight | 4 kg |

Offer Sustainability

REACH Regulation

 [REACH Declaration](#)

EU RoHS Directive

Not applicable, out of EU RoHS legal scope
