1.2 Gbps Wi-Fi Mesh Router Dual-band 802.11ac Wave 2 (100Mbps Uplink) 57MM-WR01



The 57MM-WR01 is a Wi-Fi meshing router offering speeds up to 300 Mbps over 2.4 GHz and 867 Mbps over 5 GHz Wi-Fi channels. With the 4 x 5dBi omnidirectional antennas, the WR01 provides a strong and consistent Wi-Fi signal throughout your home or office. In addition, you can easily build your home or office network using MESH technology while managing and supporting the system via the free cloud-based app.

Ruijie

Features and Benefits

- » Dual-band 802.11ac Wave 2 support speeds up to 1167 Mbps (100Mbps Uplink)
- » MESH technology for seamless roaming between units
- » Simple setup and network management at your fingertips with the Reyee Router app
- » 4x4 MU-MIMO with four high-performance 5dBi omnidirectional antennas
- » Perfect for connecting smart home Wi-Fi devices to the internet with built-in flexible parental controls
- » 1x WAN, 3x LAN (RJ45 10/100Base-T)



1.2 Gbps Wi-Fi Mesh Router Dual-band 802.11ac Wave 2 (100Mbps Uplink) 57MM-WR01





57MM-WR01 Specifications

Hardware specifications	
Wireless specifications	2.4GHz 2*2: maximum rate 300Mbps;
	5GHz 2*2: maximum rate 867Mbps Antenna: External SdBi omnidirectional antennas
	Support 802.11 a/b/g/n/ac/ac Wave2,
	MU-MIMO
	Frequency band: Independent 2.4GHz and 5GHz modules, supporting dual frequency
	integration
	Wi-Fi channel:
	2.4GHz :2.4G~2.4835GHz
	5GHz: 5.150~5.250GHz, 5.250~5.350H, 5.4 70~5.725GH, 5.725~5.850GHz (According to
	country specific)
Ports	1 10/100M WAN port (Auto MDI/MDIX) 3 10/1 00M LAN ports (Auto MDI/MDIX) 1 white
	system LED indicator, 1 WIFI LED indicator, 4 network port LED indicators 1 device
	pairing/factory reset button
	1 power input interface
Physical specifications	Dimensions: 182x120x32mm (Wx Dx H, excluding antennas)
	Weight: 0.4kg (entire equipment including packaging)
Power supply	Power specification: DC12V 1 A Maximum power: <7W
Certification	CE, RoHS
Operating environment	Operating temperature: 0-45°(Storage temperature: -40-70°(Operating humidity: 5%-
	95%RH (non-condensing)
	Storage humidity: 5%-95%RHn (non-condensing)
Main features	Routing mode: PPPoE / DHCP / static IP; relay mode: wired relay / wireless relay
	Obtain PPPoE account from the old router Wi-Fi dual-band separation/integration Guest
	Wi-Fi; smart Wi-Fi; wireless network isolation
	Static DHCP address
	Virtual server: port mapping, DMZ, etc. DONS: Oray
	UPnP
	Wireless security: WPA-PSK/WPA2-PSK encryption
	ARP protection: IP/MAC binding
	SSID hiding
	Preventing rogue devices (Blacklist/whitelist) Internet access control
Advanced features	Reyee Mesh: Supports zero-configuration networking of multiple devices, and supports
	automatic switching between wired and wireless networking for multiple devices Wi-Fi
	optimization: Wi-Fi roaming, SG priority, acceleration mode, channel adjustment, power
	adjustment, roaming sensitivity adjustment
	Bandwidth management: intelligent bandwidth allocation
	Auto network inspection, fault diagnosis Software upgrade: Automatic & manual cloud
	software upgrade
	Software applicate
Management mode	Local web page