

Product data sheet

Characteristics

EVP2CNS163C4

Attached Cable T2 16A 3-Ph IEC 4 meters -
Wallbox EVH2 spare part



Main

Range	EVlink
Product or component type	Charging cable
Accessory / separate part category	Spare part
Network number of phases	Three phase
Poles description	3P + N
[In] rated current	16 A
[Us] rated supply voltage	380...415 V AC 50/60 Hz
Earthing system	Compatible TN Compatible IT with additional isolation transformer on the power supply Compatible TT
Nominal output power	11 W 16 A
Socket number	1

Complementary

Connector type	T2 vehicle end silver plated contacts Without connector charging station end
Range compatibility	EVlink EVlink Wallbox EVH2 charging station
Standards	IEC 62196-2 IEC 62196-1
Product certifications	CE
Length	4 m
Net weight	3.1 kg

Environment

IP degree of protection	IP54 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262
Ambient air temperature for operation	-30...50 °C
Ambient air temperature for storage	-40...80 °C
Relative humidity	5...95 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15 cm
Package 1 Width	30 cm
Package 1 Length	40 cm
Package 1 Weight	1.582 kg

Offer Sustainability

REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes