

Product data sheet

Specifications



EVlink Charging cable 10m 32A 1-Phase T2-T1 IEC EV accessory

EVP1CNX32121

Main

Range	EVlink
Product or component type	Charging cable
Accessory / separate part category	Cabling accessory
Network number of phases	Single phase
Poles description	1P + N
[In] rated current	32 A
[Us] rated supply voltage	220...240 V AC 50/60 Hz
Socket number	2

Complementary

Plug type	T1 / silver plated contacts charging station end
Connector type	T2 charging station end silver plated contacts T1 vehicle end silver plated contacts
Range compatibility	EVlink (EVlink parking) EVF1 charging station EVlink (EVlink parking) EVW1 charging station EVlink (EVlink parking) EVF2 charging station EVlink (EVlink parking) EVW2 charging station EVlink (EVlink Smart Wallbox) EVB1 charging station EVlink (EVlink Wallbox) EVH2 charging station
Standards	IEC 62196-1 IEC 62196-2
Product certifications	CE
Length	10 m
Net weight	4.1 kg
Colour	Grey

Environment

IP degree of protection	IP44 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262
Ambient air temperature for operation	-30...50 °C
Ambient air temperature for storage	-40...80 °C
Relative humidity	5...95 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	16 cm
Package 1 Width	35 cm
Package 1 Length	40 cm
Package 1 Weight	4.07 kg
Unit Type of Package 2	S04
Number of Units in Package 2	2
Package 2 Height	30 cm
Package 2 Width	40 cm
Package 2 Length	60 cm
Package 2 Weight	9.392 kg
Unit Type of Package 3	P06
Number of Units in Package 3	8
Package 3 Height	75 cm
Package 3 Width	60 cm
Package 3 Length	80 cm
Package 3 Weight	46.068 kg

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes

Recommended replacement(s)