

PRODUCT DATASHEET LED CCT SELECTABLE STICK 9 W/3000 K/4500 K/6500 K E27

LED PERFORMANCE STICK TRI CCT | LED lamps with classic stick shape and TruWave



Areas of application

- All domestic rooms, especially where the lamps are visible
- Wherever compact and efficient lamps are needed
- Where the lamps need to last a long time or have to withstand frequent on/off switching

Product benefits

- TRI Colour 3000K/4500K/6500K
- LED lamps with innovative TruWave Technology™
- Support sleep/wake cycle thanks mimic of the natural light spectrum
- The balanced blue light spectrum can support attention, reaction time and mood
- Low energy consumption

Product features

- Color rendering index R_a: ≥ 80
- Lifetime: up to 15,000 h
- Mercury-free lamps



TECHNICAL DATA

Electrical data

Nominal wattage	9 W
Construction wattage	9.00 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	70 W
Nominal current	60 mA
Type of current	AC
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor λ	> 0.50

Photometrical data

Luminous flux	900 lm
Nominal useful luminous flux 90°	900 lm
Luminous efficacy	100 lm/W
Lumen main.fact.at end of nom.life time	0.70
Color temperature	3000 K/4500 K/6500 K
Color rendering index Ra	> 80
Light color	830/845/865
Standard deviation of color matching	≤6 sdcm

Light technical data

Beam angle	170 °
Starting time	< 0.5 s

Dimensions & Weight

Overall length	107.00 mm
Diameter	40.00 mm
Maximum diameter	40 mm
Product weight	38.00 g

Temperatures & operating conditions

- emperatures a specialist contactions			
Ambient temperature range	-20+40 °C		
Lifespan			
Number of switching cycles	100000		
Additional product data			
Base (standard designation)	E27		
Mercury content	0.0 mg		
Capabilities			
Dimmable	No		
Certificates & Standards			
Type of protection	IP20		
Standards	CB		
Photobiological safety group acc. to EN62778	RG1		
Country-specific categorizations			
Order reference	LPSTICK9W/830/8		
Energy labelling regulation data acc EU 2019/2015			
Light source cap-type (or other electric interface)	E27		

DOWNLOAD DATA

Length

Height

Width

Photometric and lighting design files
IES file (IES)
LDT file (Eulumdat)
LDC typ polar
LDC typ polar

107.00 mm

40.00 mm

40.00 mm

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854082108	Folding box 1	42 mm x 42 mm x 113 mm	55.00 g	0.20 dm³
4099854082115	Shipping box 10	226 mm x 96 mm x 134 mm	608.00 g	2.91 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.