

## FIREBREAK DUCT R1.0



Polyaire Firebreak Flexible Duct is manufactured from metalized Mylar and clear Mylar substrates, incorporating totally enclosed helically wound galvanised high tensile steel wire. The layers are bonded with a fire retardant adhesive to ensure long life in all ambient conditions.

The insulation is a polyester thermal blanket manufactured to rigid standards.

### Features

- Metalized Inner Core
- Polyester Insulation
- Metalized Outer Fire Jacket
- Operating Temperature: -20°C to +80°C
- Operation Pressure: -190pa to +1200pa
- General Use: Heating and cooling
- Domestic and commercial systems
- Complies with AS 4254
- Test certificates available

### Firebreak Duct R1.0 (Polyester Insulation) - 3 Metre Lengths

Sizes Available/Dimensions			
Item #	Diameter		Length (m)
	mm	inch	
110017	Ø 150	Ø 6"	3
110019	Ø 200	Ø 8"	3
110021	Ø 250	Ø 10"	3
110023	Ø 300	Ø 12"	3
110025	Ø 350	Ø 14"	3
110027	Ø 400	Ø 16"	3
110029	Ø 450	Ø 18"	3
110030	Ø 500	Ø 20"	3
110043	Ø 550	Ø 22"	3
110031	Ø 600	Ø 24"	3

### Firebreak Duct R1.0 (Polyester Insulation) - 6 Metre Lengths

Sizes Available/Dimensions			
Item #	Diameter		Length (m)
	mm	inch	
110018	Ø 150	Ø 6"	6
110020	Ø 200	Ø 8"	6
110022	Ø 250	Ø 10"	6
110024	Ø 300	Ø 12"	6
110026	Ø 350	Ø 14"	6
110028	Ø 400	Ø 16"	6
110127	Ø 450	Ø 18"	6
110213	Ø 500	Ø 20"	6

All sales are made on the basis of the 'Polyaire Terms and Conditions of Trade' ©2016 Polyaire™ Pty Ltd. The manufacturer reserves the right to alter product specifications without notice. E. & O.E. Conditions Apply.