

Product data sheet

Specifications



Enclosure, EVlink Pro AC Metal, IP66, pedestal mount in metallic kit enclosure, for 25mm² to 35mm² cable

EVA1RFKES

Main

Range	EVlink
Product name	EVlink Pro AC Metal
Product or component type	Enclosure
Range compatibility	EVlink (EVlink Pro AC) EVB3 charging station
Poles description	3P + N
Mounting mode	Assembled
Localisation on device	On lower part
Rated supply voltage	380...415 V AC 50/60 Hz 220...240 V AC 50/60 Hz
Earthing system	TT TN-S TN-C-S IT Compatible IT with additional isolation transformer on the power supply

Complementary

Provided equipment	1 mounting plate 2 DIN rail 4 fixing bracket 3 cable gland
DIN rail length	240 mm
Mounting plate description	Telequick perforated
Cable entry number	2 cable gland for M32 1 cable gland for M12
Cable cross section	25...35 mm ²
Height	360 mm
Width	270 mm
Depth	180 mm
Net weight	3.4 kg

Environment

IP degree of protection	IP66
IK degree of protection	IK09
Ambient air temperature for operation	-30...70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	19.000 cm
Package 1 Width	29.000 cm
Package 1 Length	38.500 cm
Package 1 Weight	3.270 kg
Unit Type of Package 2	P12
Number of Units in Package 2	40
Package 2 Height	110.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	153.500 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Recommended replacement(s)