

Concrete screw pan head Phillips® Ø 6.5 x 32 mm (x100)



Characteristics

Head Type : **Pan head**
 Ø (mm) : **6.5**
 Length (mm) : **32**
 Concrete C20/C25 shear load (daN*) : **22**
 Concrete C20/C25 tensile load (daN*) : **75**
 Plasterboard 12 mm tensile load (daN*) : **19**
 Plasterboard 12 mm shear load (daN*) : **27**
 Woodboard 9 mm shear load (daN*) : **19**
 Woodboard 9 mm tensile load (daN*) : **27**
 Quantity per box : **100**

Materials

- ☑ Concrete
- ☑ Wood
- ☑ Plasterboard

GENERAL INFORMATION

Technical details

Zinc plated.
 Pre-drilling : 5 mm.
 PH2 drive.

Advice

Pre-drilling required for concrete C20/C25.

Application(s)

For fixing in concrete, wood and drywall.

LOGISTIC INFORMATION

Packaging



Carton box

Height (cm) : 12
 Length (cm) : 9
 Depth (cm) : 3,5
 Net weight (kg) : 0,44
 Gross weight (kg) : 0,45



Outer package 1



x 30.00

Carton box

Height (cm) : 18
 Length (cm) : 38
 Depth (cm) : 19
 Gross weight (kg) : 13,64



Outer package 2



x 1500.00

Pallet

Height (cm) : 110
 Length (cm) : 120
 Depth (cm) : 80
 Gross weight (kg) : 707

