

## Product data sheet

### Characteristics

# CLITPDL1C3

## LED downlight, Clipsal - Lighting, 750lm, 3K/4K/6K, white



### Main

|                           |                           |
|---------------------------|---------------------------|
| Range                     | Clipsal                   |
| Product or component type | Downlight                 |
| Device application        | Lighting                  |
| Market segment            | Residential<br>Commercial |
| Main colour tint          | White                     |
| Colour tint               | White                     |

### Complementary

|                        |   |
|------------------------|---|
| Device mounting        | Recessed ceiling  |
| Shape                  | Round   |
| Type of installation   | Indoor/outdoor  |
| Rated power in W       | 7 W   |
| Light source           | LED   |
| Total system power     | 230 V AC 50 Hz  |
| Luminous flux          | 750 Lm 3000 K warm white<br>750 Lm 4000 K cool white<br>750 Lm 6000 K day light |
| Colour rendering index | R <sub>a</sub> =80  |
| Bulb lifespan          | 50000 h   |
| Beam angle             | 90 °  |
| Load type              | Dimmable LED  |
| Quantity per set       | 1   |
| Trim width             | 110 mm  |
| Cut-out dimensions     | 90 mm   |
| Mounting depth         | 55 mm   |
| Product weight         | 0.2 kg  |

### Environment

|                                       |                          |
|---------------------------------------|--------------------------|
| IP degree of protection               | IP44                     |
| Insulation contact rating             | IC-4                     |
| Unified glare rating                  | < 22                     |
| Ambient air temperature for operation | -10...25 °C              |
| Relative humidity                     | 10...95 % non-condensing |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 9 cm     |
| Package 1 Width              | 13 cm    |
| Package 1 Length             | 13 cm    |
| Package 1 Weight             | 264 g    |
| Unit Type of Package 2       | CAR      |
| Number of Units in Package 2 | 24       |
| Package 2 Height             | 30 cm    |
| Package 2 Width              | 27.5 cm  |
| Package 2 Length             | 54 cm    |
| Package 2 Weight             | 6.972 kg |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product                         |
| REACH Regulation           | <a href="#">REACH Declaration</a>             |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>        |
| RoHS exemption information | <a href="#">Yes</a>                           |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a> |
| Circularity Profile        | <a href="#">End Of Life Information</a>       |

## Contractual warranty

|          |        |
|----------|--------|
| Warranty | 3-Year |
|----------|--------|