



## WIDELINE SL9733TC/DP - 9W/55W

LED wide diffused batten 9 - 55 watt with selectable CCT and power

### Application

Low profile design suitable for residential apartments and commercial service spaces

### Design Specifications

- Wide pressed steel base with opal polycarbonate diffuser
- Quality white powder coated finish
- High efficiency LED optics, CRI >80, beam distribution 120°
- Integral constant current non-dimmable LED driver, with selectable power
- Selectable CCT 3000K / 4000K / 5700K
- Large terminal block for easy installation






### Performance

- Dimmable - **NO**



### Technical Specification

Product	Model No.	Input Voltage (V/AC)	Multiple Wattage	Lumens (lm)	CCT (K)	CRI
	SL9733/206TC/DP	240	9/18	2100/2300/2200	3000/4000/5700	80
	SL9733/212TC/DP	240	18/36	3800/4150/3900	3000/4000/5700	80
	SL9733/215TC/DP	240	28/55	5900/6350/6100	3000/4000/5700	80

Beam Angle (°)	Dim (mm)	Body Colour	IPART
120	610(L) x 160(W) x 63(H)	WHITE	N/A
120	1145(L) x 160(W) x 63(H)	WHITE	N/A
120	1495(L) x 160(W) x 63(H)	WHITE	N/A

NOTE: Lumens (lm) shown are at full power setting

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".