

# Product data sheet Characteristics

## A9A26904

Auxiliary contact, Acti9 A9A, iOF, 1 C/O, 100mA to 6A, 24VAC to 415VAC, 24-130 VDC, bottom connection





#### Main Range of product Acti9 Product or component OC contact type Device short name iOF 1 C/O Signal contacts composition [In] rated current 0.1...6 A at 24...240 V, AC 50/60 Hz 0.1...3 A at 415 V, AC 50/60 Hz 0.1...6 A at 24 V, DC 0.1...2 A at 48 V, DC 0.1...1.5 A at 60 V, DC

0.1...1 A at 130 V, DC

1

### Complementary

I	
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	4 kV
Mounting mode	Clip-on
Mounting location	Left side of circuit-breaker
Mounting support	DIN rail
Comb busbar and distribution block compatibility	Top: YES
Height	86 mm
Width	9 mm
Depth	73 mm
Net weight	32 g
Colour	White
Connections - terminals	Screw clamp terminal (bottom) 1 cable(s) 14 mm² - rigid Screw clamp terminal (bottom) 1 cable(s) 0.52.5 mm² - flexible Screw clamp terminal (bottom) 2 cable(s) 2.5 mm² - rigid Screw clamp terminal (bottom) 2 cable(s) 1.5 mm² - flexible with ferrule
Wire stripping length	10 mm
Tightening torque	1 N.m bottom

9 mm pitches

#### **Environment**

Standards	EN/IEC 60947-5-1	
	GB/T 14048.5	
Product certifications	CE[RETURN]UKCA	
Quality labels	EAC	
	CCC	
	CMIM	
IP degree of protection	IP20	
Pollution degree	3	
Tropicalisation	2	
Relative humidity	95 % at 55 °C	
Ambient air temperature for operation	-3570 °C	
Ambient air temperature for storage	-4085 °C	

23/05/2024

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.100 cm
Package 1 Width	8.000 cm
Package 1 Length	9.300 cm
Package 1 Weight	41.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Height	8.500 cm
Package 2 Width	10.000 cm
Package 2 Length	27.000 cm
Package 2 Weight	570.000 g
Unit Type of Package 3	S03
Number of Units in Package 3	120
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	6.300 kg

## Offer Sustainability

Oner oustainability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₽¥Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Life Is On