



ECOSTAR II GIMBAL S9146TC2 - 10W

Dimmable, GIMBAL 10 watt LED downlight with selectable CCT.

Application

Ideal for any residential or commercial interior space

Design Specifications

- Durable die-cast aluminium body profile 30° gimbal
- Stylish white powder coat finish
- High output LED optics
- Multi-faceted reflector system, 60° beam distribution
- Polycarbonate optical lens
- Remote, trailing edge dimmable LED driver, with flex and plug, double insulated, white surface mount options available, 145hm, x Ø152mm (S9146SM/TC2WH)



Performance

- Dimmable - **YES**
- Dimmer Type - **Trailing edge, optional 1-10V, DALI / DSI**



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	Beam Angle (°)
	S9146TC2WH	240	10	750/900/850	3000/4000/5700	60
	S9146SM/TC2WH	240	10	750/900/850	3000/4000/5700	60

Dimmable	CRI	Body Colour	Cut Out (mm)	Diameter (mm)	Dim (mm)
YES	80	WHITE	92	103	55(H)
YES	80	WHITE		152	145(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

