




ALL-IN-ONE EXIT LUMINAIRE

EGRLPG2



Technical Specification

System Performance	
Operating Voltage/ Frequency	230V / 50Hz
Power (Normal)	2.3W
Light Source	LED

Luminaire Construction	
Body	Polycarbonate
Dimensions (LxHxW)	325 x 204 x 79 mm
Weight	1.0kg
IP Rating	IP20
Temperature	0°C to +45°C

Emergency Mode - Maintained	
Power (EM)	2.3W
Battery Type	LiFePO4
Battery Specification	3.2V 1.5Ah
Battery Part No.	EGRLPG2-BAT
Classification	C0: E5.0 / C90: E5.0

Installation	
Mounting	Ceiling, Wall Mount (Standard) Rod Mount, Chain Suspension, Wall Side Mount (Accessories Required)

Warranty	
Luminaire	3 Years
Battery	2 Years

Features:

- High output LEDs for bright consistent & efficient light distribution.
- Lithium Iron Phosphate battery including integrated battery management system (BMS) to maximize battery life.
- Complete with all variations of the “Running Man” decal pack with a 24m viewing distance.
- Range of mounting options available (additional accessories may be required).
- Designed and manufactured in accordance to AS/NZS 2293.



ALL-IN-ONE EXIT LUMINAIRE



EGRLPG2

Mounting Options	
<p>Chain Suspension Mounting Accessory Kit: EGRLPG2-CS</p>	
<p>Rod Mounting Accessory Kit: EGRLPG2-RM</p>	
<p>Wall Side Mounting Accessory Kit: EGRLPG2-WS</p>	

