

FSC Series – Straight Swivel Fittings (Brass)

- Two (2) component nickel plated brass straight non-compression swivel fitting.
- Provides maximum protection for electrical installations in Industrial & Commercial environments.

Product Details:

| | |
|-------------------|--|
| Temperature range | - -45°C to + 135°C |
| Material | - Nickel Plated Brass |
| Protection degree | - IP40 |
| Characteristics | - High tensile strength, oil and corrosion resistant - Multi-part two (2) component non-compression swivel fitting - External male metric thread |
| U.V. Protection | - U.V. Resistant |
| Compatibility | - Interchangeable and adaptable with Adaptaflex SP and Flexicon FSU ranges |
| Applications | - Suitable for threaded and knock out entries. |



| Product Catalogue No. | Thread Dimensions | Nominal Conduit Size (mm) | Thread Length (mm) | Inside Diameter (mm) | Outside Diameter (mm) | Total Length (mm) |
|-----------------------|-------------------|---------------------------|--------------------|----------------------|-----------------------|-------------------|
| FSC16-B-SW | M16 X 1.5 | 16 | 12.7 | 10.4 | 28 | 36.7 |
| FSC16/20-B-SW | M20 X 1.5 | 16 | 12.7 | 10.4 | 28 | 36.7 |
| FSC20-B-SW | M20 X 1.5 | 20 | 12.7 | 13.5 | 32 | 36.7 |
| FSC25-B-SW | M25 X 1.5 | 25 | 14.2 | 18.5 | 39 | 39.3 |
| FSC32-B-SW | M32 X 1.5 | 32 | 16.3 | 24.9 | 47 | 43.3 |
| FSC40-B-SW | M40 X 1.5 | 40 | 18.2 | 33.4 | 60 | 51.2 |
| FSC50-B-SW | M50 X 1.5 | 50 | 18.2 | 37.8 | 67 | 51.2 |