

Product No: MSB121230DDG

IDE IDE55 ROLLED MILD STEEL DOUBLE DOOR WALL MOUNTED
ENCLOSURE 1200Hx1200Wx300Dmm GREY MSB121230DDG

FEATURES

- Cold-rolled steel EN 10130+A1
- Injected polyurethane sealing gasket
- Primer coated and hardened RAL 7035 polyester paint, embossed, with UV protection
- Substitute G with A for orange colour RAL 2008
- Mounting plate included



| General Information | |
|---------------------------------|--|
| Brand | IDE |
| Customs Tariff Number | 85.38.10.00 |
| EAN | 8431044033945 |
| ETIM 8.0 | EC000261 |
| Product End of Life | It does not require specific recycling operations. |
| Product Type | Wall-mounting Cabinet |
| Technical Attributes | |
| Application | Industrial environments, manufacturing companies requiring a high degree of protection against dust, splashes and impacts. |
| Maximum Operational Voltage (V) | 1000 AC / 1500 DC |
| Physical Attributes | |
| Ambient Temperature Range (°C) | -25 to +60 |
| Cable Entry (mm) | 2 x (125H x 485W) |
| Colour | RAL 7035 |
| Door Profiles | 4 |
| Door Type | Double |
| Finish | Coated with primer, and hardened polyester paint, textured, with UV protection |
| Installation | Surface |

| | |
|------------------|--|
| Lock Type | 5-mm double-bit lock – One 3-point lock |
| Material | Cold-rolled steel EN 10130+A1 |
| Mounting Plate | With flat mounting plate. 2-mm galvanised sheet steel |
| No. of Hinges | 6 |
| No. of Locks | 3 points |
| Sealing Gasket | Injected polyurethane sealing gasket |
| Supply | Supplied in individual packaging containing cabinet, plate and accessory bag. Mounting plate is supplied assembled inside the cabinet. |
| Type of Door | Double opaque door. Reversible |
| Wall Fixing (mm) | 760H x 960W |

Dimensions

| | |
|----------------------------|---|
| Dimensions (mm) | 1200H x 1200W x 300D |
| Mounting Plate Size (mm) | 1170W x 1150H |
| Thickness (mm) | Enclosure: 1.5 Door: 2 Cable entry lid: 2 |
| Usable Internal Space (mm) | 1150H x 1150W x 279D |
| Weight (kg) | 89.4 |

Protection & Standards

| | |
|---------------------------|------------------------|
| Certifications | UL508A |
| Degree of Protection | IP55 |
| Directive | 2014/35/EU |
| NEMA Degree of Protection | NEMA 1, 12 |
| Rated Impact Resistance | IK10 |
| Standards | IEC 62208, IEC 61439-1 |
| Sustainability | RoHS – REACH |

Resources

| | |
|------------------------------|------------------------------------|
| Product catalogue (Flipbook) | Download from here |
|------------------------------|------------------------------------|