

Eaton 170M3121

Catalog Number: 170M3121

Fuse-link, high speed, 500 A, AC 690 V, compact DIN 1, 45 x 59 x 104 mm, aR, DIN, IEC, type K indicator



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M3121
	Model Code
	FUSE 500A 690V 1*KN/80 AR UC
EAN	UPC
5027590444019	051712254908
Product Length/Depth	Product Height
305 mm	65 mm
Product Width	Product Weight
145 mm	317 g
Warranty	Compliances
Not Applicable	CE Marked RoHS Compliant
Certifications	
IEC Rated UL Recognized	

Product specifications

Interrupt rating

200 kAIC

Clearing loss

70

Center-to-center distance of connections

76.4 mm

Insulated metal gripping lugs (IMGL)

No

Current type

AC

Mounting method

DIN 43 620

Amperage Rating

500 A

Fuse type

DIN 43653

KN/80 Type K Indicator for Micro

Bolted tag

Fuse system (according to IEC 60269)

Other

Fuse size

1*

Voltage rating

690 V (IEC), 700 V (UL)

Fuse indicator

Centre fuse status indicator

Construction size

Other

Clearing (I²T)

180000 at 660 V

Rated voltage AC

690 V

Color

None

Connection

Blade end x blade end

Resources

Compliance information

UKCA Fuse-links for the protection of semiconductor devices, sz1* up to 630A

CE Fuse-links for the protection of semiconductor devices, sz1* up to 630A

Technical data sheets

720014 DIN 43653 690V

Mounting dimension

M10

Utilization category

aR (accompanied semiconductor protection)

Watt losses

70 W

Type

Fuse

Fuse shape

Square body, slotted center bolted tags

Breaking capacity

200 kA

Class

Class aR

Pre arc (I²T)

27000

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Voltage type

AC

Packaging type

Standard



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)