





Bondi

1200mm Double Diffused/Wireguard Emergency Batten

The Bondi series LED batten lights are the perfect solution for projects and economic applications, utilising a replaceable Kwicky module for unparalleled ease of maintenance. Optional Beacon Bondi motion sensor available for a range of lighting-control and energy-saving applications.












Features

-  4,000 Lumens
-  Tri-Colour
-  LiFePO₄ Lithium Battery
-  Kwicky Replaceable Emergency Modules

Accessories

- Replacement Kwicky: EMP-KWICKY-EM
- Motion Sensor: SENSOR-BONDI
- Wireless Motion Sensor: BEACON-BONDI
- Replacement Diffuser: DIFF-1200-BONDI
- Replacement Wireguard: WIRE-1200-BONDI

	 emergency	 self-test	 networking
ORDER CODE	BONDI-1200-2-W-EM BONDI-1200-2-D-EM	BONDI-1200-2-W-ST BONDI-1200-2-D-ST	BONDI-1200-2-W-LR BONDI-1200-2-D-LR
WARRANTY	3 Years	5 Years	5 Years
TRADITIONAL DROP TEST			
APP SCHEDULED TESTING			
REMOTE SCHEDULED TESTING			



Download the Elumen app



Device Specifications

OPERATIONAL INFORMATION

VOLTAGE	220 - 240VAC
FREQUENCY	50Hz
LUMINOUS FLUX	4000lm (Wireguard) 3850lm (Diffused)
POWER CONSUMPTION	43W
AMBIENT TEMPERATURE	1°C - 40°C
IP RATING	IP20
COLOUR TEMPERATURE	3000K / 4000K / 5000K
MOUNTING TYPE	Surface Ceiling
OPERATING MODE	Switch Controlled, Maintained, Non-Maintained
PROJECTED LED LIGHT SOURCE LIFE	100,000 Hours

CONSTRUCTION, DIMENSIONS AND WEIGHT

CONSTRUCTION	White Powder Coated Steel Body, Polycarbonate Diffuser
WEIGHT	3.2kg
CARTON QTY	4
CARTON DIMENSIONS	1,260mm x 280mm x 220mm
CARTON WEIGHT	15.8kg

COMPLIANCE AND TESTING

STANDARDS	AS/NZS 2293.3	AS/NZS 60598.2.22	AS/NZS CISPR 15
EMERGENCY CLASSIFICATION	Diffuser: - C0: D63 - C90: D12.5	Wireguard: - C0: D50 - C90: D25	

Product Drawing

