**ipd**

## Product No: MST202090G

### IDE IDE66 MILD STEEL TERMINAL BOX WITH PLAIN SIDES & SCREW-ON COVER 200Hx200Wx90Dmm MST202090G

#### FEATURES

- - Cold-rolled steel EN 10130+A1
- - Injected polyurethane sealing gasket
- - Coated with hardened RAL 7035 polyester paint, embossed, with UV protection
- - Mounting plate not included
- - According to low tension directive 2014/35/EU
- - Complies with: UNE-EN 62208
- - UL Certificate UL508A

### General Information

| | |
|---|---|
| Brand | IDE |
| Customs Tariff Number | 85.38.10.00 |
| EAN | 8431044016658 |
| ETIM 8.0 | EC002713 |
| Product End of Life | It does not require specific recycling operations. |
| Product Type | Steel terminal box with plain sides |

### Technical Attributes

| | |
|---|---|
| Application | Industrial environments, manufacturing companies requiring a high degree of protection against dust, splashes and impacts. |
| Maximum Operational Voltage (V) | 1000 AC / 1500 DC |

### Physical Attributes

| | |
|---|---|
| Ambient Temperature Range (°C) | -25 to +60 |
| Colour | RAL 7035 |
| Finish | Coated with hardened polyester paint, textured, with UV protection |
| Installation | Surface |
| Lock Type | Lid fastened with fast jackscrew with watertight caps |

| | |
|---|---|
| Mounting Plate | Without mounting plate. 2 side brackets |
| Sealing Gasket | Injected polyurethane sealing gasket |
| Supply | The body, cover and accessory bag are supplied shrink-wrapped. |
| Type of Door | Opaque lid |
| Wall Fixing (mm) | 160H x 160W |

## Dimensions

| | |
|---|---|
| Dimensions (mm) | 200H x 200W x 90D |
| Thickness (mm) | 1.2 |
| Usable Internal Space (mm) | 175H x 175W |
| Weight (kg) | 2 |

## Protection & Standards

| | |
|---|---|
| Certifications | UL508A |
| Degree of Protection | IP66 |
| Directive | 2014/35/EU |
| NEMA Degree of Protection | NEMA 1, 4, 12 |
| Rated Impact Resistance | IK10 |
| Standards | IEC 62208 |
| Sustainability | RoHS - REACH |

## Resources

| | |
|---|---|
| Product catalogue (Flipbook) | Download from here |