

## ECO Panel Gen3


# ECOPL123CSLSEG3

- Slim, energy efficient backlit LED panel with a sleek and modern appeal.
- 3 in 1 Colour Select and Lumen Select allowing you to choose the right colour temperature and light level adjustment for the application.
- Comes with a microprismatic diffuser for comfortable and low glare lighting.



#### LUMEN SELECT COLOUR SELECT

#### Line Drawings



#### **Product Images**



#### Performance

System Power	25W, 34W
Exit Lumen	2887lm, 3724lm, 3877lm, 3552lm, 2962lm, 2771lm
Efficacy	110lm/W
ССТ	4000K, 5000K, 6500K
CRI	80
Operating Temperature	0 to 40
UGR Design	19
MacAdam Steps	3SDCM
Ingress Protection Rating	IP40
Impact Rating	IK03
Warranty	5 Years
Lifetime	54,000hrs (L70/B50)
Turtle Friendly	No

### Physical

,	
Dimensions	L1193.50 x W293.50 x H32 mm
Diffuser	Polystyrene
Luminaire Colour	White
Weight	1.9kg
Luminaire Material	Cold Rolled Steel
Driver Location	Remote
Installation	Recessed

#### Electrical

Voltage	240V
Line Voltage Frequency	50Hz
Inrush Current	17.5A
Inrush Current Duration	520µs
Line Current	0.11A
Surge protection	Yes
Electrical Rating	Class II



#### Accessories

FRM/PM18W	Plaster frame to mount in plaster ceiling - White, 600x300mm (sold separately)
FRM/PM18WIDE	Plaster frame to mount in plaster ceiling - White, 600x600mm (sold separately)
FRM/PM36W	Plaster frame to mount in plaster ceiling - White, 1200x300mm (sold separately)
FRM/PM36WIDE	Plaster frame to mount in plaster ceiling - White, 1200x600mm (sold separately)
UDFRM/6-3	Universal Deep Surface Mount Frame 600X300X70 (sold separately)
UDFRM/6-6	Universal Deep Surface Mount Frame 600X600X70 (sold separately)
UDFRM/12-3	Universal Deep Surface Mount Frame 1200X300X70 (sold separately)
UDFRM/12-6	Universal Deep Surface Mount Frame 1200X600X70 (sold separately)
WIRESUSP/ECOPL	Suspension Kit - Includes 2 sets for 1 panel (sold separately)