



ECOSTAR S9046TC - 9W

Dimmable 9 watt GIMBAL LED downlight, with selectable CCT.

Application

Ideal for any residential or commercial interior spaces

Design Specifications

- Durable die-cast aluminium body profile
- Stylish powder coat finish in white or plated satin nickel
- Versatile gimbal head with 30° tilt
- High output LED optics, CRI > 80
- Selectable CCT 3000K/4000K/5700K
- Remote, trailing edge, dimmable LED driver with flex and plug, white surface mount options available, 145hm, x Ø152mm (S9046SM/TC/WH), IC - 4 rated, double insulated



Performance

- Dimmable - **YES**
- Dimmer Type - **Trailing edge. Optional - 1-10V, DALI / DSI**



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	Beam Angle (°)
	S9046TC/WH	240	9	800/800/850	3000/4000/5700	60
	S9046TC/SN	240	9	800/800/850	3000/4000/5700	60
	S9046SM/TC/WH	240	9	800/800/850	3000/4000/5700	60

Dimmable	CRI	Body Colour	Cut Out (mm)	Diameter (mm)	Dim (mm)	IPART
YES	80	WHITE	92	103	60(H)	N/A
YES	80	SATIN NICKEL	92	103	60(H)	N/A
YES	80	WHITE		152	145(H)	N/A

REES
N/A
N/A
N/A

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

Dimensions

