

Product No: LC12PIX12-65

IDE LOAD CENTRE IP65 1 X 12 MOD TRANSPARENT LID RAL7035 WITH E+N BARS LC12PIX12-65

FEATURES

- Sealable watertight distribution box
- Grey (RAL 7035) colour
- Transparent window
- Maximum operating temperature: -25°C to 40°C
- Maximum operating voltage: 1000V AC / 1500V DC
- IP65 Degree of Protection



General Information

Brand	IDE
Product Type	Polycarbonate Enclosure

Technical Attributes

Ball Pressure Test (°C)	70
Class of Insulation	Class II (Double Insulation)
Glow Wire Resistance (°C)	650
Maximum Operational Voltage AC (V)	1000
Maximum Operational Voltage DC (V)	1500
Rated Current (A)	125

Physical Attributes

Ambient Temperature Range (°C)	-25°C to 40°C
Cable Entry	Top: 2 x M25 - 2 x M32 - 1 x M40 Bottom: 6 x M20 - 2 x M25 - 2 x M32 - 1 x M40 Int.: 4 x M25 Oblong Rear: 2 x OB 25/32/25
Colour	RAL 7035
Lid Material	Tinted PC, UV Protection
Material	Halogen-free Plastic
Mounting Type	Surface Mount
Window Type	Transparent

Dimensions

Dimensions (mm)	310W x 246H x 148D
No. of Modules	1 x 12 DIN Rail
Weight (kg)	1.42

Protection & Standards

Degree of Protection	IP65
Rated Impact Resistance	IK08
Standards and Approvals	IEC 62208, Directive 2014/35/EU AS/NZS 61439.3:2016 Appendix ZZ Clauses 10.101 and 10.102 AS/NZS 3000 Clause 2.10.4.2, IEC 62208 Directive 2014 35/EU Compliant

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------

DIMENSIONS

